

DESCRIPTION

692 Medallion with a luminous perforated or solid edge detail which provides a soft uniform glow.

Catalog #		Type
Project		
Comments		Date
Prepared by		

SPECIFICATION FEATURES

Material

Painted or plated cold-rolled steel base metal. Matte white acrylic lens.

Finish

Standard: Matte White (MW) or Matte Black (MB). Premium: Satin Chrome (SC), Polished Chrome (PC), Satin Brass (SB), Polished Brass (PB), Oxidized Brass (OBRS), Polished Copper (PCP), Satin Copper (SCP), Satin Nickel (SN), Polished Nickel (PN), Lacquered Satin Chrome (SCL), Lacquered Satin Nickel (SNL) or Custom Color (CC).

Optics

Refer to www.shaperlighting.com for complete photometrics.

Ballast

Integral electronic HPF, multi-volt 120/277V (347V Canada), thermally protected with end-of-life circuitry to accommodate the specified lamp wattage.

Lamp/Socket

One (1) 22W or 40WT5 circular fluorescent lamp or two (2) 40W frosted A-19 lamps. Fluorescent socket injection molded plastic. INC socket fired ceramic rated for 660W-250V. Lamps furnished by others.

Installation

Supplied with a universal circular strap for a standard 4" J-box or plaster ring.

Options

Solid Metal Perimeter Trim (ST), Remote Emergency Battery - Supplied by others (REM), Hand Painted Faux Alabaster Diffuser (FD), Damp Location (DL): All Painted Finishes, Lacquered Satin Chrome (SCL) and Lacquered Satin Nickel (SNL) finishes only. Energy Star Rating - Consult factory. MRI Applications (INC only) - Contact Factory.

Labels

U.L. and C.U.L approved for indoor and damp location. See options for damp location finishing requirements. ADA compliant.

Modifications

Shaper's skilled craftspeople with their depth of experience offer the designer the flexibility to modify standard wall luminaires for project specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors, or decorative detailing.



692 SERIES

Interior Wall Luminaire
Medallion



ORDERING INFORMATION

Sample Number: 692-INC/2/40-120V-PB

Series	Lamp	Voltage	Finish	Options
692 =Medallion	INC/2/40 T5C/1/22 T5C/1/40	120V 277V ¹ 347V ¹	<u>Standard</u> MB=Matte Black MW=Matte White <u>Premium</u> CC=Custom Color OBRS=Oxidized Brass PB=Polished Brass PC=Polished Chrome PCP=Polished Copper PN=Polished Nickel SB=Satin Brass SC=Satin Chrome SCL=Lacquered Satin Chrome SCP=Satin Copper SN=Satin Nickel SNL=Lacquered Satin Nickel	DL=Damp Location REM=Remote Emergency Battery ² FD=Hand Painted Faux Alabaster Diffuser TR=Trim Ring

Notes:

¹ Available with CFL only.

² Supplied by others.

ADA AMERICAN DISABILITIES ACT (ADA)

Shaper offers a large selection of ADA interior and exterior wall luminaires. ADA requires all fixtures below 68" to have a maximum projection of 4".

ENERGY STAR

Shaper now offers a wide variety of fixtures that can be provided with an Energy Star Rating.

MRI MAGNETIC RESONANCE IMAGING (MRI)

Lighting fixtures for MRI facilities are specialized and unique, requiring non-ferrous construction. Fluorescent fixtures cannot be used due to the ferrous parts in ballasts and lampholders. Modified incandescent fixtures meet the requirements.

Refer to the Icon Legend
Link on shaperlighting.com.

